MODELS

hp p1130 CRT monitor (carbon/silver)

Part Numbers:
302270-003
P4819 #xxx Rest of World

SPECIFICATIONS

Tube Type	FD Trinitron® aperture grille tube			
Picture Tube Size (diagonal)	21 inch (53.3 cm)			
Viewable Image Area (diagonal)	19.8 inch (50.3 cm)			
Aperture Grille Pitch	.24 mm			
Horizontal Frequency (kHz)	30 to 130 kHz			
Vertical Frequency (Hz)	50 to 170 Hz			
Maximum Resolution	2048 x 1536 @ 75Hz			
Maximum Pixel Clock Speed	< 370 MHz			
Preferred Flicker Free Resolution	1920 x 1440 @ 85 Hz			
Preset Graphic Modes (non-interlaced)	1920 x 1440 @85Hz	1800 x 1440 @80Hz	1600 x 1200 @75, 85Hz	1280 x 1024 @75, 85Hz
	1024 x 768 @75, 85Hz	800 x 600 @75, 85Hz	640 x 480 @65, 75 and 85Hz	640 x 400 @ 70Hz
User-Modes	8 preset modes and 10 additional modes			
Anti-Glare/Anti-Static	Yes/Yes			
AssetControl	Yes			
Front Panel User Controls	Power on/off switch; 5-button OSD; dual-input switch			
Languages	**Nine**	English, French, German, Spanish, Italian, Dutch, Swedish, Russian, Japanese		
On-Screen User Controls	**Size and Positioning**	Yes		
	Contrast	Yes		
	Brightness	Yes		
	Moiré Correction	Yes		
	Tilt (rotation)	Yes		
	Selectable Colour temperature	Yes		
	Orthogonality	Yes		
	Degauss	Yes (automatic at power on; manual)		
	Convergence (h/v/pre-set)	Yes		
	Reset	Yes		

Downloaded from www.Manualslib.com manuals search engine

SPECIFICATIONS *(continued)*

Approvals/Certifications	**UL/CSA/CUL Approval**	Yes
	ISO9241-3, -7, -8 VDT Guidelines	Yes
	MPR-II Compliant	Yes
	TCO '99	Yes
	FCC Approval	Yes
	Microsoft WHQL Certified	Yes
	Energy Star Compliant	Yes
	CE Compliant	Yes
Plug and Play	VESA DDC2Bi and DDC2B. PC2001 compliant	
Dual Input	Yes, two 15-pin D-sub connections	
Signal Cable	Detachable 15-pin D-sub mini connector	
Power Supply	Universal; 100–240 V (auto-ranging), 50–60 Hz	
Maximum Power Rating	135 Watts	
Low Power Sleep Mode	< 3 Watts	
Off Mode	0 Watts	
Dimensions (H x W x D)	**Unpacked**	19.7 x 19.6 x 19.3 in (50.2 x 49.7 x 49.0 cm)
	Packaged	26.0 x 26.0 x 26.0 in (66.0 x 66.0 x 66.0 cm)
Weight	**Unpacked**	67.2 lb (30.5 kg)
	Packaged	72.5 lb (32.9 kg)
Tilt / Swivel Base	–5 to +15 degrees vertical tilt; +/–45 degrees horizontal swivel	
Operating Temperature	50° to 104° F (10° to 40° C) non-condensing	
Operating Humidity	10% to 80% non-condensing	
Altitude	**Operating**	0 to 13,000 ft (0 to 4,000 metre)
	Non-Operating	0 to 50,000 ft (0 to 15,250 metre)
Warranty	Limited three-year parts and repair labour, service provider labour, and on-site service. Next Business Day advanced exchange direct replacement service available during warranty period. Certain restrictions and exclusions apply. For details, consult the Product Information Centre at 1-888-882-6672.	

©2002 Hewlett-Packard Canada. All rights reserved. Printed in Canada.

HP shall not be liable for technical or editorial errors or omissions contained herein. The information is provided "as is" without warranty of any kind and is subject to change without notice. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty.

Downloaded from www.Manualslib.com manuals search engine